

EXPLORER 710

High-Speed, Portable BGAN Terminal



Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



Specifications

Di	m	er	ารเ	ioi	ns	

Total H / W / D: 332 / 279 / 54 mm 13.07 / 10.98 / 2.13 inches

Total weight: 3.5 kg / 7.7 lbs (incl. battery) Antenna: 1.9 kg / 4.2 lbs Transceiver (incl. battery): 1.6 kg / 3.5 lbs

Global Services

4 kbps AMBE+2 Premium voice: 3.1 kHz audio, 64 kbps Standard IP: Up to 492 kbps Streaming IP: 32, 64, 128 kbps (256 kbps & BGAN X-Stream)

High Data Rate Streaming: Min. 600 kbps

Min. 300 kbps (Half-channel HDR)

ISDN: UDI 64 kbps / RDI 56 kbps

SMS: Not supported

1518.0 - 1525.0 MHz (Rx) (EMEA) Inmarsat frequencies: 1525.0 - 1559.0 MHz (Rx)

> 1626.5 - 1660.5 MHz (Tx) 1668.0 - 1675.0 MHz (Tx) (FMFA)

EIRP: 20dBW ±1dB

User Interface: PMOLED Display, 5 navigation keys.

Audio and LCD pointing aids and LED

indicator, Compass

Languages: UK, FR, DE, ES, RU and CN

Approvals: Inmarsat Class 1 Type Approval at launch CE & FCC at launch. Other approvals TBC





Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

Interfaces

1 x Analogue RJ-11 phone/fax interfaces

2 x LAN (RJ-45) interface

PoE Cl. 2 on one RJ-45 interface Power over Ethernet: 100m / 328ft (Cat5 UTP) Max. cable length:

1 x USB host interface

2.0 (host), Charging up to 2A

1 x ISDN interface

Connector type: RI-45

Max. units per port: 8, max. total power supplied 1W

1 x Transceiver / Antenna interface

Connector type: TNC-TNC Max. cable loss: 1.4 / 20dB @ 1.5GHz

1 x BGAN SIM-Card slots

WLAN Access Point

Standard: IEEE 802.11 b/g

Environmental conditions

Temperature

Operational (ambient): -25°C to +55°C / -13°F to +131°F Storage (excl. battery): -40°C to +80°C / -40°F to +176°F

Battery storage temperature

 -20° C to $+60^{\circ}$ C / -4° F to $+140^{\circ}$ F 1 month: 3 months: -20°C to +45°C / -4°F to +113°F -20°C to +20°C / -4°F to +68°F 1 year:

Water and dust: Transceiver: IP52 / Antenna: IP66

Relative humidity: 95% non-condensing at +40°C / +104°F

Power

DC input range: 10-32VDC

Power consumption

Intelligent Power Management 65W (max.)

AC/DC power supply

100-240VAC, 47-63Hz, 65W Input: 19VDC Output:

Connector type: 2.5 / 5.5 mm power jack

Battery: Lithium ion, rechargeable Stand-by time: 24 hours (to be confirmed) Transmit time, max.: 2h30m @ 144 kbps (25°C / 77°F) 1h30m @ 650 kbps 3h30m @ 492 kbps Receive time, max.:

Subject to change without further notice

Other features

Built-in SIP server

Embedded Webserver

Advanced Router with admin control

Wireless Access Point

Battery hot-swap and Built-in BGAN bonding Remote activation and remote management

EXPLORER Connect App for IOS and Android:

Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

EXPLORER Cellular Modem for USB:

With the EXPLORER LTE Modern you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

403720B-100 EXPLORER 710 Antenna 403686G Lithium Ion Battery 403720B-010 Battery Hot Swap Cable 403682P 100-240V AC/DC Power Supply 403650A-009 Car Charger Cable 403670A-00500 IP Handset incl. Cradle 403650A-921 Pole Mount Kit 403720B-942 10m Antenna Cable 403720B-945 30m Antenna Cable 403720B-947 50m Antenna Cable 403756A-0500 EXPLORER Cellular USB Modem

Product number

EXPLORER 710 Terminal 403720B-00500

For further information please contact:

Cobham SATCOM Lundtoftegaardsvej 93 D DK-2800 Kgs. Lyngby Denmark

Tel: +45 3955 8800 Fax: +45 3955 8888